



Suffix : 後綴代號意義

G	: Fixed Type Without Fixing Ring	固定側免固定圈	OL	: Oil Lubrication	油循環功能軸承座
H2	: 2 Round Holes In Feet	底座2圓孔	WJ	: Water Jacketed Design	水循環功能軸承座
H4	: 4 Round Holes In Feet	底座4圓孔	RO	: Without Fixing Ring	不帶固定圈
J1	: Housing Feet Ends Machined	底座兩端端面加工	R1	: With 1 Fixing Ring	帶1固定圈
X	: With Inner Box	軸承座有內紙盒裝	R2	: With 2 Fixing Ring	帶2固定圈
J	: Housing Feet Machined Flat	底座真平面加工	R4	: With 4 Fixing Ring	帶4固定圈
Y	: With Cap Bolt Grade8.8	結合螺絲中碳鋼8.8級			
K	: Special Shaft Dia. To Be Specified.				特殊軸徑
N1	: 1 Grease Nipple Connection Hole, 1 Grease Escape Hole				1注油孔, 1洩油孔
N2	: 2 Grease Nipple Connection Holes, 2 Grease Escape Holes				2注油孔, 2洩油孔
N3	: 1 Grease Nipple Connection Hole, 2 Grease Escape Holes				1注油孔, 2洩油孔
N4	: 2 Grease Nipple Connection Holes, 1 Grease Escape Hole				2注油孔, 1洩油孔
N5	: 3 Grease Nipple Connection Holes, 1 Grease Escape Hole				3注油孔, 1洩油孔
N6	: 1 Grease Nipple Connection Hole, 4 Grease Escape Holes				1注油孔, 4洩油孔